

DMS

Dynamic Motion Sensors

Accurate motion measurement in all sea conditions

The DMS range of motion sensors is designed specifically for the motion measurement needs of the marine industry. Whether it is achieving IHO standard survey from any size of vessel, or providing safety critical monitoring of offshore platforms, large vessels, helicopter landing decks, cranes and positioning systems, the DMS provides accurate motion measurement in all sea conditions.

Incorporating an enhanced external velocity and heading aiding algorithm for improved accuracy during dynamic manoeuvres, the solid state angular rate sensors offer reliability in the highest performing vertical reference units ever produced by TSS.



Subsea



Surface

PRODUCT FEATURES AND BENEFITS

- Dynamic roll and pitch accuracy from 0.05° to 0.50° RMS
- Heave accuracy ±5cm or 5%
- Solid state solution available in surface and subsea housings
- Survey to Class 1 IHO standard
- High dynamic accuracy during vessel turns
- High reliability
- Power and data over Ethernet (surface units)
- Independently configurable serial outputs
- Complies with IEC 60945
- 24 hour, 365 days/year technical support
- Intuitive control software with user-configurable outputs
- Real-time digital and analogue outputs
- Compact and lightweight
- Low power, cost-effective solutions

DMS

Dynamic Motion Sensors

The DMS range of sensors is available in surface or subsea variants - the subsea unit is rated to 3000m as standard with 6000m available on request. As with all TSS systems, the DMS is certified to meet all current and anticipated European legislation for electromagnetic compatibility and electronic emissions.

The latest DMSView software programme is an intuitive Windows™ - based programme enabling installation, set-up and integrity checking, and monitoring of the sensor. The user can select from a series of frequently used data protocols or configure a bespoke output from a selection of variables.

Product	Dynamic Accuracy	Depth Rating	Heave	Roll	Pitch
DMS-05	0.05°		✓	✓	✓
DMS-10	0.10°		✓	✓	✓
DMS-25	0.25°		✓	✓	✓
DMS-525	0.25°	X	✓	✓	✓
DMS-550	0.50°	X	✓	✓	✓
DMS-550RP	0.50°	X	X	✓	✓
DMS-535RP	0.35°	X	X	✓	✓
DMS-525RP	0.25°	X	X	✓	✓
DMS-RP25	0.25°	✓	X	✓	✓
DMS-500H	X	X	✓	X	X

No formal restrictions for most countries although heave products are subject to Export License.



Heave, Roll, Pitch

The DMS range of motion sensors is designed specifically for the motion measurement needs of the marine industry. Whether it is achieving IHO standard survey from any size of vessel, or providing safety critical monitoring of offshore platforms, large vessels, helicopter landing decks, cranes and positioning systems, the DMS provides accurate motion measurement in all sea conditions.

Incorporating an enhanced external velocity and heading aiding algorithm for improved accuracy during dynamic manoeuvres, the solid state angular rate sensors offer reliability in the highest performing vertical reference unit ever produced by TSS.



DMS-05
Subsea

PRODUCT FEATURES AND BENEFITS

- Dynamic roll and pitch accuracy to 0.05°
- Heave ±5cm
- Survey to Class 1 IHO standard
- High dynamic accuracy during vessel turns
- Surface and depth rated options available
- Intuitive control software with user-configurable outputs
- Real-time digital and analogue outputs
- Compact and lightweight

Roll, Pitch

The DMS-RP sensors meet the requirements of the dynamic positioning industry for accurate vessel roll and pitch measurement. The units provide accurate motion measurement in all sea conditions.

Incorporating an enhanced external velocity and heading aiding algorithm for improved accuracy during dynamic manoeuvres, the solid state angular rate sensors offer reliability and a complimentary blending algorithm has proven that the DMS is the highest performance vertical reference unit ever produced by TSS.

The DMS-RP sensors are available in Subsea and Surface versions.

The sensors can be supplied in various configurations for integration with towed vehicles and other bespoke applications. As with all TSS systems, the DMS is certified to meet all current and anticipated European legislation for electromagnetic compatibility and electronic emissions.



DMS-RP25
Subsea

PRODUCT FEATURES AND BENEFITS

- Dynamic roll/pitch accuracy from 0.05° to 0.50° RMS
- Heave accuracy ±5cm or 5%
- Surface and subsea options available
- Independently configurable serial outputs
- Power and data over Ethernet (surface only)
- Survey to Class 1 IHO standard
- High dynamic accuracy during vessel turns
- DMSView intuitive control software
- User-configurable outputs
- Real-time digital outputs
- Compact and lightweight

Heave

Whether in ports and harbours, offshore or as part of a hydrographic mapping programme, the need to measure ocean depths with the utmost accuracy is vital.

The DMS-500H heave sensor has been developed to work with a wide range of modern single beam echosounders. With their design allowing acceptance of correction data from the DMS-500H, real-time heave compensation of the sounder data is now achievable. Providing heave data in analogue and digital format, the outputs of the DMS-500H are easily configurable via a simple operator menu.

Compact, ruggedised and quick to install, the sensor is supplied with the cable connector necessary for interfacing and is accompanied by a comprehensive operation manual.

In addition to echosounder compensation, the DMS-500H is ideally suited to a wide range of offshore applications including crane and winch control, wave radar and ship motion measurement.

Covered by a comprehensive warranty, the DMS-500H also has free technical telephone support for the total life of the product.



PRODUCT FEATURES AND BENEFITS

- Measurement to meet IHO standards
- Provides cost savings by increasing weather windows for survey
- Solid state accelerometers and rate sensors
- Accurate real-time heave data
- Removes vertical motion errors from survey data to eliminate the need for post-processing
- Suitable for a wide variety of vessels
- Free telephone support for life of product
- Designed to provide operators with the optimum cost benefit solution
- IP 65 Rated



DMS

Dynamic Motion Sensors

TECHNICAL SPECIFICATIONS

	DMS-500H	DMS-05	DMS-10	DMS-25 DMS-525	DMS-550	DMS-RP25 DMS-525RP	DMS-535RP	DMS-550RP				
DYNAMIC ACCURACY												
Heave	5cm or 5% whichever is greater					N/A						
Roll & Pitch (°RMS)	N/A	0.05	0.10	0.25	0.50	0.25	0.35	0.50				
Export Compliance (ECCN)	7A003d					No Licence Required						
	DMS-05, DMS-10, DMS-25, DMS-RP25				DMS-500 Range							
Maximum Calibrated Range	Heave ±10m, Roll & Pitch ±30°											
Data Resolution	Heave 1cm, Roll & Pitch 0.01°											
Bandwidth	Heave 0.05 to >10Hz, Roll & Pitch 0 to >10Hz											
DATA OUTPUT RATE												
Digital	Up to 100Hz											
Analogue	Up to 500Hz (with external repeater)				N/A							
Available Output Parameters	Adjustable data output packet output rate down to 1Hz. Heave, roll pitch, remote heave, angular rate (X, Y, Z); acceleration (X, Y, Z – body frame); angular rate east north up; acceleration east north up (geographical frame); IMU temperature, surge, sway, sensor status, external speed, external heading, UTC time				Adjustable data output packet output rate down to 1Hz. Heave, roll pitch, angular rate (X,Y,Z); acceleration (X,Y,Z-body frame); sensor status							
DIMENSIONS												
Size	99mm (dia) x 172mm (h) excluding connector				160mm x 160mm x 160mm (240mm max at base)							
Weight	2.3kg (3000m), 4.0kg (6000m)				4.0kg							
Depth Rating	3000m standard, 6000m on request				IP65							
Power Supply	12-36Vdc (2A supply)											
Power Requirement	<6.5W				<12W							
Power Over Ethernet	N/A				IEEE 802.3AF-2003							
Temperature Range	0°C to 55°C operating, -20°C to 70°C storage				-15°C to 55°C operating, -20°C to 70°C storage							
Shock (survival)	30g peak (40ms half sine)											
Vibration (operating)	IEC 60945				IEC 60945							
INPUT PACKET FORMATS												
Velocity	NMEA0183 (VTG & GLL or GGA), TSIP (DMS-05, -10, -25), Doppler speed log				NMEA0183 (VTG & GLL or GGA)							
Heading	NMEA0183, SGB, Robertson; Sperry LR40/60				NMEA0183 (DMS-550)							
Output Data Formats	TSS1, TSS1 with RH, TSS3, TSS Post Heave, Simrad EM1000 and EM3000, Simrad EM1000 and EM3000 with RH, Atlas, Atlas with RH, NMEA PR DID, BMT1, Polled Output, PSXN, User Configurable											
INTERFACE												
Digital	RS232 or RS422 (software selectable)				RS232 or RS422 (software selectable), Ethernet							
Analogue	Via remote control interface for power, communication and aiding				N/A							
Ethernet	N/A				Dual redundant interfaces. Packet output via TCP, UDP or UDP multicast							
Topside Software	DMSView for Windows™ or DMS500View for Windows™											
Mean Time Between Failures	50,000 hours											
Quality	ISO9001, ISO14001											
Warranty	12 months international warranty including parts and labour.											

COMPANY WITH
MANAGEMENT SYSTEMS
CERTIFIED BY DNV
= ISO 9001 =
= ISO 14001 =

Specifications subject to change without notice.
© 2012 Teledyne TSS, Inc. All rights reserved.



TELEDYNE TSS
Everywhereyoulook™

www.teledyne-tss.com

Head Office
1 Blackmoor Lane,
Croxley Green Business Park,
Watford, Hertfordshire
WD18 8GA, UK
Tel: +44 (0)1923 216020
Fax: +44 (0)1923 216061
Email: tsssales@teledyne.com

Aberdeen
10 The Technology Centre,
Aberdeen Science & Energy Park,
Claymore Drive, Bridge of Don,
Aberdeen AB23 8GD, UK
Tel: +44 (0)1224 707081
Fax: +44 (0)1224 707085
Email: tsssales@teledyne.com

Houston
7701 West Little York, Suite 300,
Houston, TX 77040, USA
Tel: +1 713 461 3030
Fax: +1 713 461 3099
Email: tsssales@teledyne.com