



## The Latest Generation of Marine Navigation Systems

The Saturn fibre optic gyrocompass capitalises on more than a century's experience in marine navigation. Teledyne TSS' own experienced and innovative engineering team has combined the latest solid state technologies and calibration techniques to offer a user-friendly, highly accurate and cost-effective navigation solution for demanding marine environments.

The Saturn product range has been designed by TSS to provide a range of versatile attitude and heading reference, and inertial navigation systems for both surface and subsea applications. The lightweight, compact and highly reliable units have no moving parts and are maintenance free, making them ideal for all sizes of surface vessel and subsea vehicle.

Applications for the Saturn product range include navigation for fast ferries and yachts; subsea positioning for autonomous underwater, and remotely operated vehicles; attitude and heading references for dynamically positioned platforms; full attitude data for hydrographic survey vessels and much, much more.



### FEATURES & BENEFITS

- Heading, pitch, roll and heave outputs
- Full inertial position from Saturn 10
- Easy to use Saturn web interface
- Compatible with GPS, DVL, USBL and LBL
- Raw output data format supported
- Subsea titanium rated to 4000m as standard





## Navigation Systems

Saturn is the new fibre optic-based range of inertial navigation, and attitude and heading reference systems developed and manufactured by Teledyne TSS.

### APPLICATIONS

- Fast Ferries
- Yachts
- Workboats
- Survey Vessels
- Remotely Operated Vehicles
- Autonomous Underwater Vehicles



*Saturn 10  
Surface*



*Saturn 10  
Subsea*

The Saturn 10 surface and subsea systems are designed to support the offshore construction and multibeam survey industries where reliability, price and performance are essential.

The systems provide highly accurate pitch, roll, heading and heave and are suitable for a variety of applications including major seabed installations.



Saturn 30  
Surface

The Saturn 30 Surface system is designed as a solid state attitude and heading reference system (AHRS) and primary navigation sensor. The unit has no moving parts and is maintenance free – it is also lightweight, compact and highly reliable – ideal for installations where space is at a premium. It is a flexible system for all sizes of vessel and excels on smaller craft such as fast ferries, yachts and patrol craft.



Saturn 30  
Subsea

The Saturn 30 Subsea, is primarily designed for subsea ROV navigation.

All subsea versions are housed in 4000m rated titanium casings ensuring durability, reduced weight and size, and reduced corrosion when compared to aluminium casings.





## TECHNICAL SPECIFICATIONS

		SATURN 10	SATURN 30	SATURN 50	
<b>Performance</b>	Heading	<0.1° secant latitude RMS	<0.3° secant latitude RMS	<0.5° secant latitude RMS	
	Roll and pitch	0.01° RMS	0.05° RMS	0.05° RMS	
	Heave	5cm or 5%	5cm or 5%	5cm or 5%	
	Position	1nm / 8 hours TRMS	Not available	Not available	
	Alignment time	10 minutes			
	Angular rate	> 200°/s	> 300°/s	> 300°/s	
	Operating latitude	± 80°			
<b>Power</b>	Power supply	18 to 36Vd.c.			
	Power consumption	16W	14W	14W	
<b>Interface</b>	Surface	4 x configurable bi-directional RS-232 / RS-422			
		4 x configurable transmit only RS-232 / RS-422			
		1 x Ethernet			
	Subsea	Status / Alarm relay contacts			
		4 x bi-directional RS-232 / RS-422			
		4 x transmit only RS-232 / RS-422 1 x Ethernet	1 x Ethernet	1 x Ethernet	
Data formats	NMEA 0183 / IEC61162 TSS proprietary and Industry standard				
<b>Physical</b>	Dimensions	Surface	179.5mm (h) x 165mm (w) x 366mm (d)		
		Subsea	182mm (d) x 306mm (h)	157mm (d) x 280.5mm (h)	157mm (d) x 280.5mm (h)
	Weight	Surface	7.0kg	5.9kg	5.9kg
		Subsea	14.5kg / 7.2kg in water	10.2kg / 5.4kg in water	10.2kg / 5.4kg in water
	Rating	Surface	IP66	IP64	IP64
<b>Environmental and EMC</b>	Subsea	4000m titanium			
	Operating temperature	-20°C to +55°C			
	Environmental EMC	Meets or exceeds IEC60945 Meets or exceeds IEC60945			
<b>Compliance</b>	Standards	Designed to meet EU Marine Equipment Directive, US Coast Guard recognised, IMO Resolutions, IEC60945, IEC61162, IEC62288, ISO8728, ISO16328			
	Export	ECCN 7A003 (EAR re-export regulations do not apply outside of the USA)			
<b>Warranty</b>		12 months international warranty including parts and labour			

COMPANY WITH  
MANAGEMENT SYSTEMS  
CERTIFIED BY DNV  
= ISO 9001 =  
= ISO 14001 =

Specifications subject to change without notice.  
© 2015 Teledyne TSS, Inc. All rights reserved.



[www.teledyne-tss.com](http://www.teledyne-tss.com)  
Email: [tssales@teledyne.com](mailto:tssales@teledyne.com)

**Head Office**  
1 Blackmoor Lane,  
Croxley Green Business Park,  
Watford, Hertfordshire,  
WD18 8GA, UK  
Tel: +44 (0)1923 216020  
Fax: +44 (0)1923 216010

**Aberdeen**  
Silverfield House,  
Claymore Drive,  
Bridge of Don,  
Aberdeen,  
AB23 8GD, UK  
Tel: +44 (0)1224 706655

**Houston**  
10661 Shadow Wood Drive,  
Houston, Texas 77043, USA  
Tel: +1 281 710 7276  
Fax: +1 281 712 1757